

SEATING OR RECLINING FURNITURE

Background

The invention relates to furniture having a seating and/or reclining surface according to the preamble of Claim 1.

State of the Art

WO 03/030689 describes a sofa in which one or more back rest are adjustable along a rail in the form of an arc of a circle. European Patent 309 021 A also describes a sofa having various individual back rests that can be positioned. German Utility Model DE-U-20217809 describes a single pivotable back rest on a sofa which can be positioned and moved along a rail, for example. U.S. Patent A-2003/0061655 describes a sofa or bed having a pivotable back rest, optionally positionable on one or the other longitudinal side. German Utility Model DE-U-8901762 describes a sofa having two pivotable rigid back rest parts which are designed so they are adapted in shape to the seating surface which is in the form of an arc of a circle in part and can be positioned on it in various positions. Therefore the seating options can be altered by 180°. Finally, German Utility Model DE-U-9404758 discloses a sofa having a stationary back rest to which cushions can be attached adjustably.

Explanation of the Invention

The object of the present invention is to improve upon seating or reclining furniture having a back rest that can be positioned variably. This is accomplished with furniture of the type defined in the preamble, having the characterizing features of Claim 1.

Due to the fact the at least one back rest or arm rest is designed to be articulated and/or flexible itself so that it adapts in a controlled manner to the seating surface when positioned along same, largely any shape of the seating surface may be selected and nevertheless the back rest can be positioned at any point on the seating and/or reclining surface. The restriction to contours of the starting surface having a

BEST AVAILABLE COPY

simple arc shape is eliminated, and the circumference thereof may have concave or convex sections where the back rest or arm rest can be positioned.

In a preferred embodiment, the seating surface then has both concave and convex sections of the circumferential contour and the back rest(s) is/are preferably positionable along the entire circumference of the seating surface and/or reclining surface. It is thus possible to create a sofa with a direction of seating that differs by 180° and with a different shape of the free seating surface. The back rest preferably extends beneath the seating surface. It is likewise preferable if the back rest covers the end face of the seating surface, in particular covering it completely. In this way, the control means which control the bending movement of the back rest can be designed so they are not visible. In particular, this is also the case when the control means are arranged beneath the seating surface. Preferably at least one rail is provided as the control means on which at least two carriages per back rest can be moved on the rail by sliding or rolling them and are connected to the back rest. The control means are preferably designed so that they not only control the bending movement of the back rest in the movement of same but also carry the back rest and support it against the forces that occur when a user of the furniture reclines against the back rest. Furthermore, each back rest is preferably formed by five or seven elements.

Brief Description of the Drawings

Exemplary embodiments of the present invention are explained in greater detail below on the basis of the drawings, in which

Figure 1 shows a view of an item of furniture designed as a sofa according to this invention having two back rests;

Figure 2 shows the furniture from Figure 1 with back rest positioned in various positions with respect to Figure 1;

Figure 3 shows the furniture from Figure 1 and/or Figure 2 with the back rests positioned in various additional positions;

Figure 4 shows a simplified side view of a back rest and part of a seating surface and a rail and a carriage as the control means;

Figure 5 shows a schematic view of the design of a sofa with a rail and a back rest that can move along this rail;

Figure 6 shows a diagram of part of the back rest;

Figure 7 shows part of the back rest and the control means;

Figure 8 shows a carriage; and

Figure 9 shows a sliding and supporting piece for the carriage from Figure 8.

Means of Implementing the Invention

In the present patent application, preferred embodiments of the present invention are described, but it should be pointed out clearly that the present invention is not limited to these embodiments and may also be embodied in other ways within the scope of the following patent claims.

Figures 1 through 3 show schematic diagrams of one embodiment of inventive seating or reclining furniture as a sofa. This is a preferred embodiment; embodiments as strict reclining furniture (bed) or as a smaller item of seating furniture which does not allow reclining because of the size are also possible. The sofa 1 shown here has a seating surface 2 which rests on a supporting frame with the feet 8. In the example shown here, two back rests 3 and 4 are provided, but this should be understood only as an example because only one back rest or more than two back rests could also be possible. According to this invention, the back rest may be positioned in different areas of the circumference 5 of the sofa, and they bend along the adjustment path so that they adapt to the shape of the circumference, i.e., the contour of the circumference of the seating and/or reclining surface. This is readily visible in Figures 1 through 3 where the back rests 3, 4 are shifted from the position shown in Figure 1 in the direction of the

arrows shown there, the back rest 3 bending according to the highly curved circumferential contour of section 32 of edge 5 and adapting to the shape of the seating and/or reclining surface accordingly. The same thing also occurs with the back rest 4 which adapts to the less curved but also convex circumferential contour of section 31 of the edge. From the position of the back rest in Figure 2, they are then moved in the direction of the arrows in Figure 2, so the back rest 4 is moved back into the position illustrated in Figure 3 and the back rest 3 is moved further along the circumference 5 and into the concave area 30 of the circumference and also adapts to same. The positions for the back rest shown here are of course to be understood only as examples and preferably any back rest may be completely moved around the seating and/or reclining surface 2 and adapts to the circumferential contour along the entire path of travel of same. For example, starting from Figure 3, the back rest 4 could again be moved according to the arrow shown in Figure 3 until it is abutting against the back rest 3, so that the result is again a sofa having a self-contained continuous back rest like that illustrated in Figure 1 but with the seat position different by 180° because the back rest have also been moved into a position that is different by 180°. It is also possible to limit the path of travel of one or more back rest, but, as mentioned, it is preferable to move the back rest completely around the seating and/or reclining surface. An embodiment in which one or more back rest is in a fixed position and only one or more other back rest can be moved, adapting to the circumferential contour, is also possible.

The back rest preferably consist of several elements 10 that are joined together in an articulated fashion and are adapted to the circumferential contour when moved along said contour by control means.

Figure 4 shows a schematic sectional diagram of part of the exemplary embodiment that has already been explained with reference to Figures 1 through 3; the view here illustrates the area between the sections 30 and 31 of the seating and/or reclining surface 2. It can thus be seen here that this surface 33 is part of the upholstered edge 42 of the seating and/or reclining surface 2. The internal padding 43 is not shown in Figure 4 and would be situated in the recess 2' on a board 2". The back rest 4, which is shown only partially here, has been moved up

to the surface 33 in this view and can be seen with its side surface 7. The back rest 4 preferably extends over the seating and/or reclining surface 2 and in particular over its edge 42, so that the latter is covered by the back rest. It is also preferable if the back rest also covers the circumferential surface 5 of the seating and/or reclining surface 2 so that this can be seen only where the back rests are not located. As diagrammed schematically in Figure 4, the back rest 4 is now attached to the carriage 16, only one of which is illustrated in Figure 4, said carriages 16 being movable by sliding or rolling on a rail 12 so that by means of this movement of the carriages, the shape of the rail is impressed upon the back rest and/or the back rest is curved according to the shape of the rail so that the rail 12 and the respective carriages in this example are the controlling means for influencing the bending of the particular back rest.

Figures 5 through 9 show a corresponding preferred design of the furniture in greater detail. Figure 5 shows the bottom frame of the furniture in which the rail 12 extends completely around the bottom frame as a self-contained rail and at the same time forms a load-bearing element of same. This is a preferred embodiment. The rail 12 may in the meantime also be a separate element which is attached on or to another load-bearing element of the lower frame. If only partial mobility of the back rest(s) is desired, then the rail need not be self-contained and may extend over only the desired parts of the traversing path. Figure 5 in turn shows the shaping of the rail with the various convex sections and the one concave section. This shaping is of course to be understood only as an example. The inventive flexibility of the back rest allows fundamentally free shaping as part of the possible flexibility of the back rest. This in turn depends on the number and width of elements joined together in an articulated fashion or the flexibility of a flexible element, which is explained below. The lower frame of the furniture in the exemplary embodiment shown here consists not only of the rail but also the struts 13 which are attached to the rail and the bars 14 which extend upward for the seating and/or reclining surface 2 and/or the board 2" thereof. In addition, the feet 8 are attached to the lower frame. Figure 5 shows the construction of the one back rest 3, which consists of five rigid elements 20 which are joined together so they can move with hinges 15

in an articulated manner with respect to one another as depicted in greater detail in Figure 6, which shows one of the hinges in the a position in which it is raised by the elements 20. The hinge 15 (which may also be replaced by other known means for articulated connection) makes it possible to position the rigid back rest 20 of the rest 30 at an angle to one another so that the back rest 3 can adapt to the shape of the rail 12 shown here and thus to the circumferential contour of the seating and/or reclining surface as well. This means that the shape of the contour of the rail 12 will usually be the same as the circumferential contour of the seating and/or reclining surface. If desired, however, the shape of the rail may also deviate from the shape of the seating and/or reclining surface 2 so the back rest is adapted approximately to the shape of the seating surface only in certain locations. Due to the preferred coverage of the seating surface 2 by the back rest, as shown primarily here, there is nevertheless no unwanted hole between the seating surface 2 and the back rest. Figure 5 and the following figures also show the carriages 16 which are attached to the rigid back rest parts 20 and extend over the rail 12 with their other hook-shaped ends 22. As a rule, at least three carriages 16 are provided per back rest, namely one at each end and in the center so that the control means formed by the rail 12 and the carriages 16 are able to bend and/or adjust in an articulated manner the back rest following the rail as accurately as possible. More carriages may optionally also be provided, e.g., a separate carriage for each part 20. The back rest 3 shown in Figure 5 has five parts 20 having a back rest 4 (not shown here) and seven parts 20 and/or elements 10, as shown in Figures 1 through 3. As a rule, the number of elements 10 on the furniture matches the number of elements 20. In Figure 5 it can also be seen that the two parts 20 which form the end areas of the back rest are provided with side parts 17 which form the side faces 7 of the respective back rest after appropriate upholstering and covering with an upholstery material. In addition to the rigid back rest parts 20 shown here, each back rest of course also has padding and an upholstery material which form a convenient back rest in the known manner. The upholstery may be provided in one piece for the respective back rest and must of course have some elasticity and must be compressible so that the padding can follow the movement of the rigid parts 20 produced by the control means. The padding may also include a plurality of

individual parts and may have a single upholstery part for each back rest 20. The upholstery material may be selected according to the one-piece or multi-piece upholstery. The individual upholstery parts 44 are preferably partially separated from one another by appropriate seams 45 or stitching (Figure 1) and may also be visually separate parts.

The rigid parts 20 thus form a back rest that essentially does not yield when one person rests against it and/or a back rest which yields only due to its padding.

Instead of or in combination with the plurality of rigid parts 20 joined together in an articulated fashion, one or more flexible back rest parts may also be used, these parts being flexible in the direction of movement but as a rigid as possible with respect to the forces occurring when a person rests against the back rest. Corresponding back rest parts may be made of plastic and/or composite materials or metal. Instead of the control means shown here with the rail and carriages, it is of course also possible to have the back rest guided and/or controlled by a rod design having varying lengths of the rods. The rod length is adjusted, for example, by one or more control curves so that it is also possible to control the shape of the back rest according to the circumferential contour of the seating and/or reclining surface 2 in such a manner.

Figures 6 through 9 show how a carriage 16 which is made of a metal part, for example, is attached to the rigid part 20 and how sliding parts 18 made of POM plastic are preferably arranged on the holding parts 22 of the carriages extending over the rail 12. A securing part 19, which is also designed as a plastic sliding part and which extends beneath the rail, may be attached to a fastening point 63 on the carriage so that the back rest is secured against removal of the rail. Instead of sliding parts, rollers or balls may also be provided.

In the embodiment shown here, the carriages 16 of the control means together with the rail 12 at the same time form the support for the back rest 3, 4 against the forces acting on them when a person leans against them. However, this function may also be separated from the control function, as indicated in Figure 4 with the rail 12' which, as

an additional separate rail, would assume the function of supporting the back rest, so that the rail 12 only fulfills the control function. Another possible solution for this support is to provide feet 38 on the back rest, which are supported on the surface on which the sofa stands by means of spherical rollers, for example. Again in this case, the rail 12 would fulfill only the control function and the support would be provided by multiple feet 38 per back rest. Meanwhile the combined function of the rail 12 and the carriages 16 as control means and as supporting means for the back rest is preferred.

Of course the preferred arrangement of the control means shown here, i.e., the rail 12 beneath the seating surface shown in this example is to be understood only as an example. Control means could also be provided in the form of a rail on the circumferential surface 5 of the seating and/or reclining surface. The control means could also be arranged on the top side of the edge 42 of the seating surface 2, e.g., in the form of a groove-shaped hollow rail in which journals of the back rest engage, said journals protruding from the bottom side of the back rest that covers the seating surface 2. In the latter two cases, however, the control means, e.g., in the form of the abovementioned rails, are visible where the back rests are not located so that it must be embodied as a design element of the furniture accordingly.




The invention has been explained on the basis of back rest. Instead of or in addition to back rest, however, one or more arm rests may also be designed and provided according to this invention.

Patent Claims

1. Furniture (1) having a seating and/or reclining surface (2) and at least one back rest (3, 4) or arm rest connected to the former and adjustable with respect to the seating and/or reclining surface such that it can be positioned in various circumferential areas of the seating and/or reclining surface, characterized in that at least one back rest (3, 4) or arm rest is formed from a plurality of elements (10) connected in an articulated fashion and/or one or more elements that are flexible in the direction of adjustment and can be influenced to bend in the adjustment by the control means (12, 16, 18) such that the back rest or arm rest adapts itself essentially to the circumferential contour of the seating and/or reclining surface (2) along the adjustment path or at least along a part thereof.
2. Furniture according to Claim 1, characterized in that the seating and/or reclining surface (2) has a circumferential contour (30, 31, 32) that is both concave and convex.
3. Furniture according to Claim 1 or 2, characterized in that the at least one back rest or arm rest can be positioned along the entire circumference of the seating and/or reclining surface.
4. Furniture according to any one of Claims 1 through 3, characterized in that it has two separately positionable back rests (3, 4) or arm rests.
5. Furniture according to any one of Claims 1 through 4, characterized in that the at least one back rest (3, 4) or arm rest is formed from separate rigid parts (20) which are connected together in an articulated fashion by hinges (15) in the adjustment direction and they each form an element (10) with the respective upholstery, whereby the at least one back rest (3, 4) or arm rest is formed in particular by five or seven elements (10).


6. Furniture according to any one of Claims 1 through 5, characterized in that at least one back rest (3, 4) or arm rest partially covers the seating and/or reclining surface (2).
7. Furniture according to any one of Claims 1 through 6, characterized in that the at least one back rest (3, 4) or arm rest covers the circumferential surface (5) of the seating and/or reclining surface, in particular completely.
8. Furniture according to any one of Claims 1 through 7, characterized in that the control means (12, 16, 18) are arranged essentially below the seating surface.
9. Furniture according to any one of Claims 1 through 8, characterized in that the control means also support the back rest (3, 4) or arm rest and support it against the forces that occur when someone leans against it.
10. Furniture according to any one of Claims 1 through 9, characterized in that the control means include a rail (12) which determines the desired shape of bending of the back rest (3, 4) or arm rest.
11. Furniture according to Claim 10, characterized in that the rail (12) has essentially the same contour as the circumferential contour of the side face and in particular is a self-contained rail.
12. Furniture according to any one of Claims 10 or 11, characterized in that the rail is part of the understructure of the seating and/or reclining surface and in particular forms the base of the furniture with struts (13).
13. Furniture according to any one of Claims 1 through 12, characterized in that the control means comprise multiple carriages (16) which can be moved by sliding or rolling on a rail (12) for each back rest or arm rest, these carriages being attached to different elements (10) of the back rest or arm rest.

14. Furniture according to Claim 13, characterized in that the carriages include on both sides of the rail and above the rail, plastic sliding parts (18) in contact with the rail and in particular another sliding plastic part (19) which reaches beneath the rail.



2/4

FIG. 4



3/4

FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9



INTERNATIONAL SEARCH REPORT		International Application No. PCT/CH 03/00837
1. CLASSIFICATION BY SUBJECT MATTER IPC 7 A47C7/40 A47C17/04		
According to International Patent Classification (IPC) 612 2003 (classical classification and IPC)		
2. FIELD OF SEARCHING Main body of document(s) searched (classification system followed by classification symbol): IPC 7 A47C		
Supplementary searching done (not primary classification) to the extent the SLD documents are relevant to the facts asserted		
Factors that may cause during the international search (facts of the case and, where practical, search type used) EPD-internal		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Content of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 202 04 759 U (MASTROVALERIO ANEELD) 29 August 2002 (2002-08-29) the whole document	1,6,7
<input type="checkbox"/> Further documents are listed in the publication of this C <input checked="" type="checkbox"/> Please, briefly summarize the facts in annex.		
* Special categories of cited documents:		
"A" document defining the general state of the art which is not considered to be of particular relevance "C" earlier documents but published on or after the international filing date "L" document which may have claims or priority claims (or which is cited to establish the submission date of another claim or of a special reason (as specified) "D" document relating to an oral disclosure, use, exhibition or other disclosure "P" document published prior to the international filing date but later than the priority date claimed "W" document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be distinguished in respect of an inventive step from the document(s) cited "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other SLD documents, such combination being covered to a certain extent by the art "Z" document relevant to the state of the art		
Date of the actual completion of the international search		Date of filing of the international search report
18 August 2004		25/08/2004
Name and printing address of the ISA European Patent Office, P. B. 2918, Postfach 1 82535 München, Germany Tel. +31-70-340-2040, Telex: 31 640 400 04 Fax: +31-70-340-2040		Author/Office Vollerding, J

INTERNATIONAL SEARCH REPORT				International Application No.	
EISA published on patent filing process				PCT/CH 03/00837	
Parent document search report	Publication date	Parent date month(s)	Publication date	Parent date month(s)	Publication date
DE 20204759	U	29-08-2002	DE 20204759	U	29-08-2002

INTERNATIONALER RESEARCHENBERICHT

PERSONAL INFORMATION

#CT/24 02/02237

A. KASCHER, INC. 100 WILSON ST. DANBURG, CT 06810
 1PK 1 A47C37/40 A47C37/04

Magyarországi Nemzeti Színház, Budapest, 1956. (A képek a Magyar Nemzeti Színház archívumából származnak.)

D. RECOMMENDED REPORTING GUIDANCE

For more information on Mercedes-Benz, call 1-800-4-A-MERCEDES or visit our website at www.mercedes-benz.com

IPK 7 447C

[illegible]

Während die Ingenieure der Hochschule für Luftfahrt in Göttingen daran arbeiten, die Luftfahrt zu verbessern, sind die Ingenieure der Hochschule für Luftfahrt in Göttingen daran, die Luftfahrt zu verbessern.

EPO-Internal

c. als wesentliche Angelegenheit unter Planung

Einleitung: Die Veröffentlichung von Informationen über die Gesundheit von Einzelpersonen ist ein sensibles Thema.

POST-ACQUISITION LOSS

A DE 202 04 759 U (MASTROVALERIO ANGELO)
29. August 2002 (2002-08-29)
das ganze Dokument

1,6,7

☐ **Warrantless Search of Vehicle (4760.01)(b)(2)(i)(A)(ii)(I))** **Not Applicable** (If Applicable, enter the number of the vehicle searched.)

Spring Analysis Paper-Writing

* Services: Insurance, Real Estate, Investment, etc.

"A" VERIFICATION OF THE SIGNATURES OF THE OFFICIALS OF THE
UNITED STATES OF AMERICA

"I" James Edwards, son doct. 834 1st Ave. I act as informant.
Arrested by the 1st District on 10/10/41

[illegible]

404 Verleumdung, da vor der Untersuchung Aufklärung des Falls, der Untersuchungsvorgänge u. Verlaufs nicht möglich ist

[illegible]

Die Verflechtung von Wirtschaft und Politik, die bürokratische Erziehung
sowie das jugendliche Selbstverständnis sind ein Teil einer tief
verwurzelten Ideologie, die sich nicht ändern wird.

*) Verflechtung von Interessen: Entscheidung, die Interessen der Entscheidungsträger mit den Interessen der Betroffenen zu berücksichtigen. Es geht um die Verteilung von Ressourcen und um die Verteilung von Verantwortung. Die Entscheidungsträger sind in der Lage, die Interessen der Betroffenen zu berücksichtigen. Die Entscheidungsträger sind in der Lage, die Interessen der Betroffenen zu berücksichtigen. Die Entscheidungsträger sind in der Lage, die Interessen der Betroffenen zu berücksichtigen.

²¹⁰ Vertiefung der Analyse sozialer Prozesse in

[Link] Link Admin Forum - Site Information - March 16, 2017

Abstracts of the 1997 Annual Meeting of the American Society of Human Genetics

18. August 2034

25/08/2004

NAME: [REDACTED]
 ADDRESS: [REDACTED]
 CITY: [REDACTED]
 STATE: [REDACTED]
 ZIP: [REDACTED]

Erweiterung der Bestimmung

Moller, J.

INTERNATIONALER RECHERCHENBERICHT

Angaben zu Veröffentlichungen, die zur selben Patentfamilie gehören

Internationale Klassifikation

PCT/CH 03/00837

in Recherchenbericht angegebene Patentnummer	Datum der Veröffentlichung	Mitglied der Patentfamilie	Datum der Veröffentlichung
DE 20204759 U	29-06-2002	DE 20204759 U1	29-06-2002

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record.**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.